


Enterprise SSDs

Leveraging state-of-the-art BiCS FLASH™ 3D flash memory with in-house designed controllers and firmware, KIOXIA enterprise SSDs optimize high performance, endurance and reliability to run mission critical applications in enterprise data center environments. To meet the demands of highly transactional and high-bandwidth workloads, these SSDs feature high levels of performance and data protection with power-loss-protection (PLP)^{*1}. KIOXIA enterprise SSDs offer a range of security options^{*2} designed for business critical data storage.



BiCS FLASH™

Product image may differ from the actual product.

KIOXIA CM9 Series

Based on BiCS FLASH™ generation 8, the CM9 Series of dual-port PCIe® 5.0/ NVMe™ SSDs is available in 2.5-inch and E3.S form factor with capacities up to 61.44 TB. These SSDs feature Power Loss Protection (PLP) and offer a range of security/encryption options².

Model Number	DYPD ^{*3}	Interface	Form Factor	User Capacity (GB) ^{*4}	Performance (up to)				Typical Power Consumption (W)	Operating Temperature (°C) ^{*10}	Dimensions T / W / L (mm) ^{*11}
					Sequential (128 KiB) ^{*5 *6 *7} (MB/s)		Random (4 KiB) ^{*5 *6 *7 *8} (KIOPS)				
					Read	Write	Read	Write			
KCM9XVUL12T8	3	PCIe® Gen5 single x4, dual x2	2.5-inch	12,800	14,800	11,000	3,400	800	25	0 to 75	15.0 / 69.85 / 100.45
6,400				10,000							
3,200				14,500	7,000	2,900	600				
1,600					3,600	2,050	310				
KCM9XVJE12T8	3	PCIe® Gen5 single x4, dual x2	E3.S	12,800	14,800	11,000	3,400	800	25	0 to 75	7.5 / 76.0 / 112.75
6,400				10,000							
KCM9XVJE6T40				3,200	14,500	7,000	2,900	600			
KCM9XVJE3T20						1,600	3,600	2,050			
KCM9XVJE1T60	1	PCIe® Gen5 single x4, dual x2	2.5-inch	61,440	13,500	10,000	1,200	100	25	0 to 75	15.0 / 69.85 / 100.45
KCM9XRUL30T7				30,720							
KCM9XRUL15T3				15,360	14,800	11,000	3,400	540			
KCM9XRUL7T68				7,680		10,000		500			
KCM9XRUL3T84				3,840	14,500	7,000	2,900	360			
KCM9XRUL1T92				1,920		3,600	2,050	170			
KCM9XRJE30T7	1	PCIe® Gen5 single x4, dual x2	E3.S	30,720	13,500	9,750	2,750	270	25	0 to 75	7.5 / 76.0 / 112.75
KCM9XRJE15T3				15,360							
KCM9XRJE7T68				7,680	10,000	500					
KCM9XRJE3T84				3,840	14,500	7,000	2,900	360			
KCM9XRJE1T92				1,920		3,600	2,050	170			

KIOXIA CM7 Series

Based on BiCS FLASH™ generation 5, the CM7 Series of dual-port PCIe® 5.0/ NVMe™ SSDs is available in 2.5-inch and E3.S form factor with capacities up to 30.72 TB. These SSDs feature Power Loss Protection (PLP) and offer a range of security/encryption options².

Model Number	DYPD ^{*3}	Interface	Form Factor	User Capacity (GB) ^{*4}	Performance (up to)				Typical Power Consumption (W)	Operating Temperature (°C) ^{*10}	Dimensions T / W / L (mm) ^{*11}
					Sequential (128 KiB) ^{*5 *6 *7} (MB/s)		Random (4 KiB) ^{*5 *6 *7 *8} (KIOPS)				
					Read	Write	Read	Write			
KCMY1VUG12T8	3	PCIe® Gen5 single x4, dual x2	2.5-inch	12,800	7,000	2,400	550	25	0 to 73	15.0 / 69.85 / 100.45	
KCMY1VUG6T40				6,400							2,450
KCMY1VUG3T20				3,200	6,750	2,700	600				
KCMY1VUG1T60				1,600		3,500	2,000				310
KCM71VJE12T8	3	PCIe® Gen5 single x4, dual x2	E3.S	12,800	13,000	5,300	2,000	470	25	0 to 73	7.5 / 76.0 / 112.75
KCM71VJE6T40				6,400							
KCM71VJE3T20				3,200	14,000	2,700	600				
KCM71VJE1T60				1,600	3,500	2,000	310				
KCMY1RUG30T7	1	PCIe® Gen5 single x4, dual x2	2.5-inch	30,720	10,000	4,900	1,600	150	25	0 to 72	15.0 / 69.85 / 100.45
KCMY1RUG15T3				15,360							
KCMY1RUG7T68				7,680	14,000	6,750	2,450	300			
KCMY1RUG3T84				3,840			2,700	310			
KCMY1RUG1T92				1,920	3,500	2,000	155				
KCM71RJE15T3				1	PCIe® Gen5 single x4, dual x2	E3.S	15,360	13,000			
KCM71RJE7T68	7,680	6,750	2,450				300				
KCM71RJE3T84	3,840		14,000				2,700	310			
KCM71RJE1T92	1,920	3,500	2,000				155				

KIOXIA LC9 Series

Based on BiCS FLASH™ generation 8 QLC flash memory, the LC9 Series of dual-port PCIe® 5.0/ NVMe™ SSDs is available in 2.5-inch form factor with capacities up to 122.88 TB and in E3.L form factor with capacities 245.76 TB. These SSDs feature Power Loss Protection (PLP) and offer a range of security/encryption options*2.

* E3.S form factor will be available later in 2026.

Model Number	IU Size	DWPD	Interface	Form Factor	User Capacity (TB)	Performance (up to)				Typical Power Consumption (W)	Operating Temperature (°C)	Dimensions T / W / L (mm)
						Sequential (128 KiB) *5 *6 *7		Random (4 KiB) *5 *6 *7 *8				
						Read	Write	Read	Write *2			
RLC9CZB122T	16 KiB	0.3 @ 16 KiB	PCIe® Gen5 single x4, dual x2	2.5-inch	122.88	12,000	2,700	1,100	35 @ 16 KiB	25	0 to 75	15.0 / 69.85 / 100.45
RLC9CZB61T4		0.075 @ 4 KiB			61.44							
RLC9CDB30T7	4 KiB	0.25 @ 4 KiB			30.72	11,800	2,800	1,250	150 @ 4 KiB			
RLC9CZB30T7	16 KiB	0.3 @ 16 KiB 0.075 @ 4 KiB			12,000	1,350						
RLC9CZV245T	16 KiB	0.3 @ 16 KiB 0.075 @ 4 KiB	PCIe® Gen5 single x4, dual x2	E3.L	245.76	12,000	3,500	1,000	45 @ 16 KiB	30	0 to 75	7.5 / 76.0 / 142.2

KIOXIA FL6 Series

The FL6 series is a dual-port PCIe 4.0 / NVMe™ SSD utilizing low latency, high endurance KIOXIA XL-FLASH Storage Class Memory (SCM). It provides fast system response for latency-sensitive applications, such as server caching, write logging, and read / write cache for tiered storage in enterprises and hyperscale data centers.

Model Number	DWPD	Interface	Form Factor	User Capacity (GB)	Performance (up to)				Typical Power Consumption (W)	Operating Temperature (°C)	Dimensions T / W / L (mm)	
					Sequential (128 KiB) *5 *6 *7		Random (4 KiB) *5 *6 *7 *8					
					Read	Write	Read	Write				
KFL61HUL3T20	60	PCIe® Gen4 single x4, dual x2	2.5-inch	3,200	6,200	6,200	1,500	400	19	0 to 70	15.0 / 69.85 / 100.45	
KFL61HUL1T60				1,600								380
KFL61HUL800G				800								360

KIOXIA PM7 Series

Based on BiCS FLASH™ generation 5, the PM7 Series of dual-port 24G SAS SSDs is available in a 2.5-inch form factor with capacities up to 30.72 TB. These SSDs feature Power Loss Protection (PLP) and offer a range of security/encryption options*2.

Model Number	DWPD	Interface	Form Factor	User Capacity (GB)	Performance (up to)				Power Consumption Mode (W)	Operating Temperature (°C)	Dimensions T / W / L (mm)	
					Sequential (128 KiB) *5 *6 *7		Random (4 KiB) *5 *6 *7 *8					
					Read	Write	Read	Write				
KPM71VUG12T8	3	SAS-4 Narrow Single Narrow Dual	2.5-inch	12,800	4,200	4,100	720	330	9 / 12 / 14 / 18	0 to 70	15.0 / 69.85 / 100.45	
KPM71VUG6T40				6,400								355
KPM71VUG6T40				3,200								340
KPM71VUG1T60				1,600								320
KPM71RUG30T7	1	SAS-4 Narrow Single Narrow Dual	2.5-inch	30,720	4,200	4,100	720	80	9 / 12 / 14 / 18	0 to 70	15.0 / 69.85 / 100.45	
KPM71RUG15T3				15,360								160
KPM71RUG7T68				7,680								175
KPM71RUG3T84				3,840								155
KPM71RUG1T92				1,920								3,400

KIOXIA RM7 Series

Based on BiCS FLASH™ generation 5, the RM7 Series of single-port 12 Gbit/s SAS SSDs is available in a 2.5-inch form factor with capacities up to 7.68 TB. These SSDs feature Power Loss Protection (PLP) and offer a range of security/encryption options*2.

Model Number	*3 DWPD	Interface	Form Factor	*4 User Capacity (GB)	Performance (up to)				Power Consumption Mode (W)	*9 Operating Temperature (°C)	*11 Dimensions T / W / L (mm)
					*5 *7 Sequential (128 KiB) (MB/s)		*5 *7 *8 Random (4 KiB) (KIOPS)				
					Read	Write	Read	Write			
KRM7XVUG3T84	3	SAS-3 Narrow Single	2.5-inch	3,840	1,100	1,050	190	55	9	0 to 70	15.0 / 69.85 / 100.45
KRM7XVUG1T92				1,920							
KRM7XVUG960G				960							
KRM7XRUG7T68	1	SAS-3 Narrow Single	2.5-inch	7,680	1,100	1,050	190	40	9	0 to 70	15.0 / 69.85 / 100.45
KRM7XRUG3T84				3,840							
KRM7XRUG1T92				1,920							
KRM7XRUG960G				960							

*1: PLP (Power Loss Protection): In case of an unexpected shutdown, PLP allows data recorded in buffer memory to be written to flash memory, utilizing back up power from solid capacitors.

*2: Optional security features

- Drive models with different security options have different model numbers.
- CM9, CM7, LC9, PM7 and FL6 Series security options: Sanitize Instant Erase (SIE), Self-Encrypting Drive (SED), FIPS (Federal Information Processing Standards) SED optional models are available.
- RM7 Series security options: Sanitize Instant Erase (SIE), Self-Encrypting Drive (SED) optional models are available.
- CM9, CM7, LC9 and FL6 Series: SED optional model supports TCG Opal and Ruby SSCs. It has a few unsupported features of TCG Opal SSC.
- PM7 and RM7 Series: SED optional model supports TCG Enterprise SSC.
- SIE optional model supports Cryptographic Erase, which is a standardized feature defined by the technical committees (SCSI) of INCITS (the InterNational Committee for Information Technology Standards).
- FIPS SED optional models of PM7 and FL6 utilize a security module designed to comply with FIPS 140-2 and FIPS 140-3, which define security requirements for cryptographic module by NIST (National Institute of Standards and Technology). FIPS SED optional models of CM9, CM7, LC9 utilize a security module designed to comply with FIPS 140-3.
- For more details and the latest validation status of each drive, please make inquiries through "Contact us" in each region's website, <https://www.kioxia.com/>.
- Optional security feature compliant models are not available in all countries due to export control and local regulations.

*3: DWPD: Drive Writes Per Day. One full drive write per day means the drive can be written and re-written to full capacity once a day every day under the specified workload for the specified lifetime. Actual results may vary due to system configuration, usage and other factors.

*4: Definition of capacity: 1 terabyte (1 TB) = 1,000 gigabytes (GB), 1 GB = 1,000,000,000 (10⁹) bytes

*5: A kilobyte (KiB) means 2¹⁰, or 1,024 bytes.

*6: The performance of the CM9, CM7, LC9 and FL6 Series is based on single-port mode (single x4). The performance specifications of the PM7 Series is based on testing in dual-port mode, running at 18 W of power.

*7: Read and write speed may vary depending on various factors such as host devices, software (drivers, OS etc.), and read/write conditions.

*8: IOPS: Input Output Per Second (or the number of I/O operations per second)

*9: Case surface temperature

*10: Composite temperature reported by SMART.

*11: Dimensions represent the nominal values.

**1: IU Size: Indirection Unit Size. It is the minimum unit size of the FTL mapping table to manage user data on NAND flash memory.

**2: Random write performance is based on the workload of random writes with the defined IU size for each model.

Customers must refer to and comply with the latest versions of all relevant KIOXIA information, including without limitation, this document, the specifications, the data sheets and application notes for Product and the precautions and conditions set forth in the KIOXIA Corporation Reliability Handbook and the instructions for the application with which the Product will be used with or for.

All information provided in this catalog is subject to change without any prior notice. For the latest and detail specification, please send an inquiry through "Contact us" in each region's website, <https://www.kioxia.com/>.

- PCIe is a registered trademark of PCI-SIG.

- NVMe is a registered or unregistered mark of NVM Express, Inc. in the United States and other countries.

- SAS is a trademark of the SCSI Trade Association.

- Other company names, product names, and service names may be trademarks of third-party companies.